



For derusting the rail web for a continuous current flow of the flash welder or to prepare an insulated joint

- Grinding angle can be set precisely depending on the rail
- Profile grinding wheel with rotatable protective hood
- Transverse travelling gear for easy movement and positioning of the machine
- Rollers made of insulated material

TECHNICAL SPECIFICATIONS

ROGRIND P4 Web

ROGRIND E Web

Drive	4-stroke petrol engine	Electric motor 400 V/50 Hz
Type	HONDA GX 270	
Output	6.3 kW at 3600 rpm	4 kW/50 Hz at 2900 rpm
Grinding disc speed	4500 rpm	3600 rpm
Profile grinding wheel, for rails from S49		
Outside diameter	135 mm	
Inside diameter (holder)	25.4 mm (1")	
Height	90 mm	
Dimensions (L x W x H)		
Machine	1800 x 600 x 1100 mm	
Transverse travelling gear	1850 x 530 x 200 mm	
Weight, transverse travelling gear	~25 kg	~25 kg
Weight, machine	~95 kg	~98 kg

ACCESSORIES

Profile grinding wheels

- 9898081080 for rail sections S49 to R65,
135 x 55 x 90/50/25.4
- 9002000556 for rail sections smaller than S49,
135 x 55 x 70 x 20 x 25.4
- 8988980001 Conversion kit for wire brush
- 8329910001 Ballast box (for transverse travelling gear)



Conversion kit for wire brush



Profile grinding wheel