

For tightening and loosening nuts and sleeper bolts

ITS BENEFITS. YOUR BENEFITS.

Compact and robust

- Centrifugal clutch and change gear
- 1 inch square drive to accept the corresponding sockets
- Battery version 30.20 with 90° adjustable handle, particularly for wrenching brackets
- Immediate usage

Ergonomic and flexible

- Height adjustable handle with battery version 30.20
- Low vibration operation



TECHNICAL SPECIFICATIONS	ROMPACT P2	ROMPACT P2 Lowvibe	ROMPACT B
	STANDARD AIR-COOLED	LOW VIBRATION AIR-COOLED	BATTERY
	2-STROKE PETROL ENGINE	2-STROKE PETROL ENGINE	DC ELECTRICAL MOTOR
Type	without damping	with damping	without damping
Output	1.7 kW at 7120 rpm	1,7 kW at 7120 rpm	1600 W
Max. Torque	1800 Nm, depending on joint hardness	1800 Nm, depending on joint hardness	1800 Nm
			Number of tightening cycles: 500 (per 4 seconds)
Dimensions (L x W x H)	680 x 390 x 360 mm	700 x 390 x 360 mm	780 x 510 x 240 mm
Weight	~19.5 kg	~21.3 kg	~18.3 kg
Weight socket	~1.5 kg	~1.5 kg	~1.5 kg (Weight battery ~5.6 kg)

ACCESSORIES

Sockets

Hexagonal

- 8003008004 internal hex A/F 22
- 9002501208 A/F 27
- 9871033313 A/F 30
- 9871033309 hex 32
- 9002501223 A/F 34
- 9871033314 A/F 35
- 9871033311 A/F 36
- 9871033315 A/F 38
- 8098950100 A/F 39 Special 230 mm
- 9871033391 A/F 39 hex
- 9871033304 A/F 41 hex
- 9871033308 hex 42
- 9002501224 A/F 46

Rectangular

- 9871033317 rect. 18 x 26
- 9871033316 rect. 20 x 30
- 8003008006 rect. 20.5 x 24.5
- 9871033302 rect. 21 x 28
- 9871033305 rect. 30 x 22

Square

- 9871033303 sq. 19 x 19/17 x17
- 987103318 sq. 21 x 21
- 9871033306 sq. 22 x 22
- 9871033319 Socket, sq. 24 x 24

Other sockets can be found on page 68.



Socket, rect. 24 x 28 for rectangular, socket A/F 39 for hexagonal



SDS Plus chuck adapter

8099910001 SDS-Plus chuck adapter, to drill holes in sleepers

Sleeper drill bits

Max. drilling depth 150 mm with SDS-Plus chuck adapter

- 9002501808 dia. 14 mm
- 9002501809 dia. 16 mm
- 9002501810 dia. 18 mm
- 9002501811 dia. 20 mm
- 9002501812 dia. 22 mm

- 8003009006 Extension bar 180 mm/1" mounting
- 8003009005 Extension bar 330 mm/1" mounting
- 8003009007 Cardan joint 1" mounting
- 9909992145 O-ring, circlip to secure socket
- 9900070056 Dowel pin to secure socket
- 8003010003 Transport and storage box