

For tightening or loosening sleeper, hook and fishplate bolts.

# ITS BENEFITS. YOUR BENEFITS.

### **Optimum results**

- · High torque
- Electronic control for precise observance of set values
- Precise torque settings via potentiometer on control panel and visual check by operator
- 2-speed gearbox with helical gears for high efficiency
- Wrenching step carried out with push-button. Wrenching stopped automatically, thus highest accuracy and overload protection.
- Electric disc clutch for maximum durability

## **User-friendly**

 Optimum illumination of working area with LED illumination of socket integrated into the gear case

- Quick-change chuck
- Protective engine frame with carrying handles and holder for 2 sockets
- It is possible to work without outrigger due to the extremely low centre of gravity.

### Low maintenance requirement

- Due to no-maintenance electronic disc clutch
- Hardly any wear due to articulated sockets and non-friction roll behaviour for angled fasteners

### **Applications**

Can be used for all wrenching operations for various types of track construction and gauges

TECHNICAL SPECIFICATIONS	ROWRENCH P4 RKS
Drive	air-cooled 4-stroke petrol engine
Туре	HONDA GX 200
Output	4.1 kW at 3800 rpm
Spindle speed	
No-load speed	200 rpm
Load speed	70 rpm
Tightening torque indicator	max. 999 Nm
Adjustment range for screwing in	150 Nm to 350 Nm/420 Nm to 999 Nm
Loosening/tightening torque	max. 1000 Nm
Dimensions (L x W x H)	2030 x 600 x 750 mm
Weight without outrigger (outrigger 4 kg)	~92 kg



# **ACCESSORIES**

#### Transverse travelling gear

8050750001 RKS, four-wheel, instead of two-wheel monorail trolley

with outrigger, gauge 1435 mm, incl. extension

100 mm square output drive

8003082015 Four-wheel, gauge 1435 mm

8338950150 Extension, 100 mm, square output drive

Extension needed only if transverse travelling gear is ordered and supplied at a later time. When ordering a transverse travelling gear with the power wrench, the

extension is already included in the price.

8329900037 Parking brake for transverse travelling gear

9000100065 Protective hood (tarpaulin), bright yellow, made of

Trevira fabric, PVC coated, hemmed. With nickel-plated

eyelets on both long sides.

Dimensions: 1900x600x600 mm

### Fish bolt spanner

8003182001 31.82 one-sided design; without socket

8003062052 Socket, hex A/F 39 SRAUG one-sided design;

without socket

Other sockets (also articulated for straight output drive) can be found on page 68.







