



**For all drilling and wrenching tasks that arise in track construction. Especially suitable for dowel renovation.**

- Ideal for all fast wrenching tasks on rails, switches and other locations
- Powerful, robust design
- Easy operation in all work positions
- No transfer of wrenching moment to operator
- Rotates left/right
- Mechanical emergency activation of servo hydraulics
- LED work light
- With engine stop

TECHNICAL SPECIFICATIONS	ROWRENCH P4 Drill	ROWRENCH E Drill
Drive	air-cooled 4-stroke petrol engine	electric motor, 3-phase
Type	Honda GX 270	400 V, 50 Hz
Output	6.3 kW at 3600 rpm	4 kW at 2870 rpm
Spindle speed		
No-load speed	175 rpm	145 rpm
Load speed	67 rpm	55 rpm
Max. drill bit diameter	38 mm	
Max. drilling depth	180 mm	
Dimensions (L x W x H)	2100 x 600 x 750 mm	
Weight incl. outrigger	~123 kg	~139.5 kg

## ACCESSORIES

### Wooden sleeper renovation

- 1) 8913839005 MK2 (chuck) (not shown) for rail drill type 95.02
- 2) 9002501278 Drill bit dia. 43 mm
- 3) 8003083002 Tool holder to hold tools with a square drive for wooden sleeper
- 4) 9891089217 for wooden sleeper
- 5) 9891089220 Countersink for wooden sleeper dowel 15
- 6) 9891089219 Screw tap for wooden sleeper, sleeper dowel 15
- 7) 9891089227 Dowel turn-in mandrel for wooden sleeper, sleeper dowel 15
- 8) 9891085161 Turn-in tool no. 5 (spiral dowel no. 5)
- 9) 8003083003 Adapter with chuck for sleeper drill bit (wood, 96.01)
- 10) 8003083006 Depth stop



### Concrete sleeper renovation

- 11) 8910839010 MK3 (chuck) (not shown) for rail drill type 95.02
- 12) 9002501512 Drill bit dia. 29 mm, MK3
- 13) 8003083002 Tool holder to hold tools with a square drive
- 14) 8333550110 RD29 for concrete sleeper, sleeper dowels 9+13
- 15) 9891089288 Left-hand extractor for concrete sleeper, sleeper dowels 9+13
- 16) 9891089225 Dowel extraction mandrel for concrete sleeper, sleeper dowels 9+13
- 17) 9891089226 Dowel turn-in mandrel for concrete sleeper, sleeper dowels 9+13



### Replacement of corrugated dowels

- 18) 8910839015 MK4 (chuck) for rail drill type 95.02
- 19) 8003062052 Socket, hex A/F 39 SRAUG
- 20) 9002501519 dia. 38 mm MK 4
- 21) 9002501548 dia. 27 mm MK 3
- 22) 9002501513 dia. 30 mm MK 3
- 23) 8003083002 Tool holder to hold tools with a square drive
- 24) 8333550120 RD38 for wooden sleeper or corrugated dowels 1+2
- 25) 9891089218 Left-hand extractor for wooden sleeper corrugated dowels 1+2



- 26) 8330750003 Transverse travelling gear 1435 mm
- 27) 8329900037 Parking brake
- 28) 8329910001 Ballast box (for transverse travelling gear)
- 29) 8003182001 Fish Bolt Spanner 31.82, one-sided design; without socket

