

For manual lifting of sleepers. Forged steel with welded gripper angles.

Heavy duty DB design in steel.



TECHNICAL SPECIFICATIONS

ROTOOL C-Tong

Width up to	280 mm
Height up to	205 mm
Dimensions (L x W x H)	1050 x 100 x 630 mm
Weight	~10 kg

For lifting and lowering loads, e.g. track panels, rails etc. Compliant with Accident Prevention Guidelines for Winches, Lifting and Pulling Devices, BGV D8 (EN 45000).

- Solid, rugged design with large reinforced foot plate
- Safety crank with load pressure brake and foldable handle



TECHNICAL SPEC.	ROJACK Ratchet 3	ROJACK Ratchet 5	ROJACK Ratchet 7,5	ROJACK Ratchet 10
Designation	46.43	46.45	46.47	46.50
max. lifting capacity	3 t	5 t	7.5 t	10 t
max. lifting height	340 mm	300 mm	300 mm	300 mm
Partial lift per ratchet	0.8 mm	0.4 mm	0.4 mm	0.3 mm
Lift per crank handle turn	8 mm	4 mm	4 mm	4 mm
Excavation height	65 mm	65 mm	65 mm	80 mm
Dimensions (L x W x H)	290 x 220 x 715 mm	290 x 230 x 720 mm	290 x 230 x 720 mm	335 x 260 x 790 mm
Weight	~24.5 kg	~29.5 kg	~34 kg	~46 kg