

**Ensures supply of electrical power, independent from the mains supply.**

In various designs, e.g. with trolley or on transport trolley, generator output as per customer requirement.

- Design in accordance with VDE (German Association of electrical Engineers), GS certification mark
- Noise emission complies with EEC Directive 84/536 on Noise Protection
- Sound power level LWA 100 dB (A) pW
- Incl. GW 308 (ISO monitoring with switch-off), Protection type IP 54
- Protection type IP 54 with oil level monitoring
- With oil level monitoring
- Long operating times due to large tank
- CE declaration of conformity
- Operating instructions and spare parts list



TECHNICAL SPECIFICATIONS	ROPOWER P4 270	ROPOWER P4 390
Drive	4-STROKE PETROL ENGINE	4-STROKE PETROL ENGINE
Type	HONDA GX 270, with oil level monitoring	HONDA GX 390, with oil level monitoring
Output	5.4 kW at 3000 rpm	9.6 kW at 3600 rpm
Unit	fitted in a tubular protective frame with 2 lifting handles with GW 308, ISO monitoring with switch-off	fitted in a tubular protective frame with 2 lifting handles with GW 308, ISO monitoring with switch-off
Output	4 kVA/400 V and 3.7 kVA/230 V, 50 Hz	6.1 kVA/400 V and 5.2 kVA/230 V, 50 Hz
Protection type	IP 54 (protection insulated)	IP 54 (protection insulated)
Weight	~89 kg	~100 kg

TECHNICAL SPECIFICATIONS	ROPOWER PB&S	ROPOWER D
Drive	4-STROKE PETROL ENGINE	DIESEL ENGINE
Type	Briggs&Stratton, with oil level monitoring	HATZ 1B40, with oil level monitoring
Output	14.7 kW at 3600 rpm	Output 7.3 kW at 3600 rpm
Unit	with GW 308, ISO monitoring with switch-off	fitted in a tubular protective frame with 2 lifting handles with GW 308, ISO monitoring with switch-off
Output	9.0 kVA/400 V and 6.0 kVA/230 V, 50 Hz	4.7 kVA/400 V and 4 kVA/230 V, 50 Hz
Protection type	IP 54 (protection insulated)	IP 54 (protection insulated)
Weight	~134 kg	~122 kg

**ACCESSORIES**

- 9000600369 Single-axle trolley for transporting the generator, with suspension eyes and rubber handles, with 2 running wheels of 350 mm dia.
- 9008060025 Distribution box with emergency stop switch
- 9008120218 Cable drum/extension lead, approx. 30 m long
- 9008230097 Socket adapter from Euro socket CEE16A230V to Schuko socket

