

For extensive lighting of work sites

Improved work quality & safety thanks to

- Good illumination of work area
- Sturdy design and stability
- Quick and easy assembly

ROLIGHT 2x500, 2x1000

Consisting of height-adjustable light mast with 1 or 2 halogen floodlights (1000 W) Floodlights

- Telescopic mast with pneumatic hand pump
- Basket provides improved stability
- Floodlights can be swivelled up to 30°

Flexibility

Compact design, takes little space during transport and working

6 versions with varying luminosity and outputs.



TECHNICAL SPECIFICATIONS

ROLIGHT 2x0,5

ROLIGHT 2x1

Output	2 x 500 W	2 x 1000 W
Light mast height	max. 4.5 m	
Connecting cable	7 m	
Dimensions		
Light mast folded	1200 x 350 x 100 mm	
Basket folded	650 x 650 x 100 mm	
Basket (ready-to-use)	650 x 650 x 400 mm	
Weight	~43.5 kg	

Optional

Generator	3.8 kVA
Drive	4-stroke petrol engine
Type	Honda GX240
Protection type	IP 54/55
Number of sockets	2
Voltage/frequency	234 V/50 Hz

ROLIGHT KLL

Equipped with special compact fluorescent lamps with very high output at low current consumption. 4 of the 8 lamps can be turned off, providing glare-free light in one direction.

- Illuminated area of up to 700 m2
- Can withstand wind speeds of up to 120 km/h due to special stand
- Saves space and is ready for use in no time
- Supplied in impact-resistant flight case



TECHNICAL SPECIFICATIONS

ROLIGHT KLL

Version with 230VAC	
Diameter	200 mm
Length	900 mm
Lamp weight	~8.2 kg
Protection type	IP44
Protection class	I
Optimum height in use	3500 mm
Assembly time	~1 min
Stand weight	~21.5 kg
Illuminated area	700 m2
Number of lamps	8x80 W
Output	365-710 W*
Supply voltage	230 VAC
Generator power required (230VAC)	1.0 kW

*depending on operating mode

ROLIGHT LED

Suitable for all areas requiring extensive lighting. Available versions with one, two or four lamps. High light output at low power consumption.

- Maintenance-free
- Wide service temperature range: -40°C to +55°C
- No UV/IR radiation
- Extendable from 1000 to 3500 mm
- Folds down to 1000 x 190 x 190 mm



TECHNICAL SPECIFICATIONS

ROLIGHT LED

LED lamp	
LED output	40 W
Voltage	230 VAC
LED lifespan	> 50,000 h
Housing + reflector material	Aluminium
Protection type/class	IP65/I
Lamp weight	~3.3 kg
Dimensions of a lamp (L x W x H)	262 x 185 x 230 mm

ROLIGHT B LED

- Battery operated version
- Maintenance-free and no cable required
- Wide service temperature range: -40°C to +55°C
- No UV/IR radiation
- Extendable from 1000 to 3500 mm
- Folds down to 1000 x 190 x 190 mm



TECHNICAL SPECIFICATIONS

ROLIGHT B LED

Lighting duration	10 h at 100% luminosity 20 h at reduced luminosity
Charging time	6 h/100% charged
LED output	30 W
Charging voltage	230 VAC
Battery LI-ION	10 Ah 36 VDC
Luminous flux	100 lm/W
Cover	5 mm safety glass
Protection type/class of lamp and battery	IP65/III
Protection type/class of charger	IP44/I
Weight including flight case	~22 kg
Dimensions of flight case (L x W x H)	1250 x 430 x 220 mm